RS-130 and RS-160

BATTERY-OPERATED PRICE COMPUTING SCALES





800-472-6703 www.ricelake.com/retail

BATTERY-OPERATED PRICE COMPUTING SCALES

Accurate, Affordable and Portable

The RS-130 and RS-160 retail scales are the ultimate choice for simple price computing applications. Delivering unmatched convenience and accuracy, the RS-130 and RS-160 provide one-button operation with weight displays in either pounds, kilograms or ounces.

For added convenience, the RS-130 and RS-160 can toggle units of measure and save tare, price and nine direct price lookups. Cash back calculation allows you to guickly provide cash back for applications where a cash register is not present. The scales' large, stainless steel platters provide ample room for product, and standard in-use

covers assure years of trouble-free operation.

The RS-130 and RS-160 are NTEP Certified and powered by an included rechargeable battery. A low-battery annunciator signals the operator when it's time to recharge. The RS-130 and RS-160 offer the most accurate, portable and affordable solutions for simple price computing needs.



RS-160 pole model



Easy-to-read displays on the back of the RS-130 and RS-160 allow viewing by the customer.



RS-130 bench

- Toggle between pounds/kilograms/ounces
- Nine PLU keys for direct price lookups
- Cash back calculation

model pictured with backlight on

- Large, stainless steel platter
- Easy-to-read backlit displays
- In-use cover
- Battery charge indicator
- Included internal, sealed battery
- NTEP-Certified Legal for Trade

Specifications

RS-130 Capacity/ Graduations:

RS-160 Capacity/ Graduations:

30 x 0.01 lb/15 x 0.005 kg/480 x 0.2 oz 60 x 0.02 lb/ 30 x 0.01 kg/ 960 x 0.5 oz

1/3000 Accuracy:

Display Items: Weight: Five digits

Unit price: Five digits Total price: Six digits

Backlit LCD displays with 0.453-in (11.5-mm) Display Type:

character height

Zero Tracking: Automatic; center zero accuracy of ±1/2 division; maximum range of ±29

DC 6 V/25 mA rechargeable battery with AC adapter included, AC 115 V/0.1 A (max) Power Source:

Dimensions: Platter (W x D): 11.8 x 9.5 in

Bench model overall (W x D x H): 12.3 x 13.0 x 4.7 in Pole model overall (W x D x H): $12.3 \times 13.0 \times 4.7$ in

10 lb (4.5 kg)

Temperature Range:

Storage: 5° to 140° F (-15° to 60° C) **Operating:** 32° to 104° F (0° to 40° C)

Approvals

Weight:



Warranty

One-year limited warranty



