

VACUUM TABLE TOP

Models | 250 | 300 | 300D | 350 | 350D | 380 | 380T

ROBUST

This stainless steel product features quality components, including the highly reliable Busch pump.

EASY TO USE

The machine's digital display and diagnostics option make it easy to use. Only two steps are required!

CERTIFIED

The Sipromac vacuum packaging machines are ETL LISTED, CSA certified and conform to UL STD. It was designed for easy cleaning and to meet the industry's highest hygiene and food safety standards.

WHY SHOULD YOU VACUUM PACK ?

- 1 To reduce spoilage by removing air from the package resulting in much longer shelf life;
- 2 To prevent dehydration;
- 3 For ease of handling;
- 4 To slow down oxidation;
- 5 To protect against external contamination.



MODEL 250

SEAL BARS	Length	A	12.5" / 319 mm
	Qty		1
	Distance to back	B	13.1" / 333 mm
	Distance between	C	N/A
CHAMBER DIMENSIONS	Height		4" / 102 mm
BUSCH PUMP	Std.		4 m ³ 0.1 kW
	Width	E	17" / 430 mm
MACHINE DIMENSIONS	Depth	F	20.7" / 525 mm
	Height	G	17.2" / 436 mm
ELECTRICITY			120 V / 1pH / 60 Hz
MICROPROCESSOR			MC-40

VACUUM TABLE TOP

Models | 250 | 300 | 300D | 350 | 350D | 380 | 380T



MODELS 300 AND 300D

			300	300D
SEAL BARS	Length	A	19.1" / 485 mm	19.1" / 485 mm
	Qty		1	2
	Distance to back	B	15.4" / 391 mm	N/A
	Distance between	C	N/A	13.1" / 333 mm
CHAMBER DIMENSIONS	Height		6.8" / 172 mm	6.8" / 172 mm
BUSCH PUMP	Std.		20 m ³ 0.9 kW	20 m ³ 0.9 kW
	Width	E	23" / 585 mm	23" / 585 mm
MACHINE DIMENSIONS	Depth	F	23.7" / 602 mm	23.7" / 602 mm
	Height	G	19.7" / 500 mm	19.7" / 500 mm
	ELECTRICITY		120 V / 1pH / 60 Hz	120 V / 1pH / 60 Hz
MICROPROCESSOR		MC-05	MC-05	



MODELS 350 AND 350D

			350	350D
SEAL BARS	Length	A	19.1" / 485 mm	19.1" / 485 mm
	Qty		1	2
	Distance to back	B	15.4" / 391 mm	N/A
	Distance between	C	N/A	13.1" / 333 mm
CHAMBER DIMENSIONS	Height		6.8" / 172 mm	6.8" / 172 mm
BUSCH PUMP	Std.		20 m ³ 0.9 kW	20 m ³ 0.9 kW
	Width	E	23" / 585 mm	23" / 585 mm
MACHINE DIMENSIONS	Depth	F	23.7" / 602 mm	23.7" / 602 mm
	Height	G	19.7" / 500 mm	19.7" / 500 mm
	ELECTRICITY		120 V / 1pH / 60 Hz	120 V / 1pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40	

VACUUM TABLE TOP

Models | 250 | 300 | 300D | 350 | 350D | 380 | 380T



MODELS 380 AND 380T

		380	380T
SEAL BARS	Length	A 12.5" / 319 mm	12.5" / 319 mm & 32.2" / 817 mm
	Qty	2	3
	Distance to back	B N/A	12" / 306 mm
	Distance between	C 36.1" / 918 mm	36.1" / 918 mm
CHAMBER DIMENSIONS	Height	6.8" / 172 mm	6.8" / 172 mm
BUSCH PUMP	Std.	20 m ³ 0.9 kW	20 m ³ 0.9 kW
MACHINE DIMENSIONS	Width	E 42.9" / 1,090 mm	42.9" / 1,090 mm
	Depth	F 25.5" / 648 mm	25.5" / 648 mm
	Height	G 19.2" / 487 mm	19.2" / 487 mm
ELECTRICITY		120 V / 1pH / 60 Hz	120 V / 1pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40


BASIC FEATURES

- Table top single chamber
- Stainless steel construction
- Clear (see-through) lid
- Twin seal element
- Vacuum sensor - Vacuum level controlled in percentage directly with Microprocessor (except model 300-300D)
- Filler plates
- Cover latch
- Feet
- Rear panel
- Crate
- Certification; ETL listed (CSA & UL) (except model 300-300D)
- Certification; ETL Sanitation Listed (NSF)


OPTIONAL FEATURES

- Electric cut-off - Two wire seal system which outside wire cuts off excessive part of bag
- Gas injection system (MAP) - For fragile products, presentation and extending shelf life (except model 300-300D)
- Air regulator - Regulated air pressure in the seal bars bladders with compressed air (not included) (except model 300-300D)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- Inclined stainless steel filler plates for liquid
- Silencer
- Stainless Steel cart
- Other voltages available
- Service kit for standard maintenance

All features are subject to change without notice.



MC-05



MC-40

